

# Split Chamber Cvd Tube Furnace With Vacuum Station Cvd Machine

Item Number: KT-CTF12



## Introduction

Split Chamber CVD Tube Furnace with Vacuum Station - High precision 1200°C lab furnace for advanced materials research. Customizable solutions available.

[Learn More](#)

Furnace model	KT-CTF12-60
Max. temperature	1200°C
Constant work temperature	1100°C
Furnace tube material	High purity quartz
Furnace tube diameter	60mm
Heating zone length	1x450mm
Chamber material	Japan alumina fiber
Heating element	Cr2Al2Mo2 wire coil
Heating rate	0-20°C/min
Thermal couple	Build in K type
Temperature controller	Digital PID controller/Touch screen PID controller
Temperature control accuracy	±1°C
Sliding distance	600mm
<b>Gas precise control unit</b>	
Flow meter	MFC mass flow meter
Gas channels	4 channels
Flow rate	MFC1: 0-5SCCM O2 MFC2: 0-20SCCM CH4 MFC3: 0- 100SCCM H2 MFC4: 0-500 SCCM N2
Linearity	±0.5% F.S.
Repeatability	±0.2% F.S.
Pipe line and valve	Stainless steel
Maximum Operating Pressure	0.45MPa
Flow meter controller	Digital Knob controller/Touch screen controller
<b>Standard vacuum unit (Optional)</b>	
Vacuum pump	Rotary vane vacuum pump

Pump flow rate	4L/S
Vacuum suction port	KF25
Vacuum gauge	Pirani/Resistance silicon vacuum gauge
Rated vacuum pressure	10Pa
<b>High vacuum unit(Optional)</b>	
Vacuum pump	Rotary vane pump+Molecular pump
Pump flow rate	4L/S+110L/S
Vacuum suction port	KF25
Vacuum gauge	Compound vacuum gauge
Rated vacuum pressure	6x10-5Pa
Above specifications and setups can be customized	

No.	Description	Quantity
1	Furnace	1
2	Quartz tube	1
3	Vacuum flange	2
4	Tube thermal block	2
5	Tube thermal block hook	1
6	Heat resistant glove	1
7	Precise gas control	1
8	Vacuum unit	1
9	Operation manual	1